


# Straightline 36x100 Portable Radial Stacking Conveyor Unit #1240

#SN: 361000523783

- Frame: 3 x 3x 1/4" angle chords with 2 x 2 x 3/16" angle lattice members with 4 x 3 x 1/4 angle for extra chord
- Truss: 30" Deep
- Electric hydraulic power unit
- 20Ft Hydraulic powered head section fold
- SLI V-style hydraulic powered adjustable height under carriage
- Axle: Tandem w/dual 11.00-22.5R tires with FD axle single wheel for radial travel
- Air brakes and Light package
- Head pulley: 18" x 38" C.F. – 3/8" H.B. lagging – 3 7/16" shaft
- Tail pulley: 16" x 38" Wing style – 2-15/16" shaft
- Troughing idlers: CEMA C – 5" rollers on 4' centers
- Return idlers: CEMA C – 5" rollers on 10' centers
- Gear Reducer: Master PT size 6 with backstop
- Motor: 40HP 1800RPM 230/460/3ph Toshiba
- Switchgear
- 750TPH / 350FPM
- Bearings: Dodge
- Take-ups: SLI screw type
- Conveyor belt: 36"- 3 ply 3/16" x 1/16" cover
- Belt scraper: By Superior
- 5' Radial receiving hopper with extra idlers at load point
- Hitch: 5<sup>th</sup> wheel king pin and tow eye
- Pivot plate
- Guarding: Tail pulley and V-belts
- Sandblasted: Frame (1) Coat primer urethane (1) Coat finished urethane







# RBSCOTT

EQUIPMENT • WEAR PARTS • SERVICE



