

StraightLine 36" x 70' Stackable Transfer Conveyor With Roll Away Unloading System Unit #1471

#36700524873,874,875

Equipment as follows:

- 3 - 36 x 70' Transfer Conveyors - Designed to roll onto each other for one transportable system.
- Frame: 4x4x5/16" Angle - 2x2x1/4" Lattice - 3x3x3/16" Idler Mount
- 30" Deep Truss
- Adjustable Height Transfer Undercarriages on Each
- Axle (Top & Middle Conveyor): 8 Bolt Hubs - Single 11.00-22.5 Tires
- Axle (Transport Conveyor): 10 Bolt Hubs - Dual 11.00-22.5 Tires
- Head Pulley: 16" x 38" C.F. - 3/8" HB Lagging - 3 7/16" Shaft
- Tail Pulley: 14" x 38" Wing Style - 2 15/16" Shaft
- Troughing Idlers: CEMA C - 5" Rollers @ 4' Centers
- Return Idlers: CEMA C - 5" Rollers @ 10' Centers + Nip Guards
- Gear Reducer: Master PT Size 5 with Backstop
- Motor: 20HP 1800 230/460/3PH Toshiba
- Electrical Switchgear/Cords from Panel to Motor Only/Not Interlocked
- Bearings: Dodge 2 Bolt Pillow Blocks
- Take-ups: Dodge Wide Slot
- 350FPM - 750TPH
- 5' Receiving Hopper with Foldable Flared Hopper Sides
- Fifth Wheel Hitch + Tow Hook on each Conveyor
- Light Bar & Brakes Package
- Conveyor Belt 36" 3 Ply - 3/16" x 1/16" Cover
- Specifications
- Belt Splice - Flexco Mechanical Steel Fastners
- 36" Superior Belt Scraper
- Guarding: Tail Pulley, V Belts, Return Guards, Hopper
- Sandblasted, Urethane Primed, and Urethane Painted



